



Thermal Insulation Products - Wire & Wire Netting

Wire & Wire Netting

Austenitic Stainless Steel tying wire is produced from grade 304 or 316 and is available in a range of diameters to suit individual applications. Usual wire thickness is 1.2mm, however 1.6mm may be required for tying very heavy reinforcement.

Stainless Steel tying wire is often used to eliminate rust staining associated with Carbon Steel Wire encroaching into the concrete cover.

Standard coil weight is 25kg.

CONVERSION TABLE

WIRE DIA	METERS/KG	KG/1000MTR	APPROX GAUGE
0.9mm	199	5.02	20
1.2mm	112	8.93	18
1.6mm	63	15.88	16

Also available in Galvanised coils half kg coils and 25 kg coils.

Wire netting is supplied in Stainless Steel and Hot dipped Galvanised in rolls of 10mtr, 25mtr and 50mtr. Various gauges and mesh sizes available.

HOT DIPPED GALVANISED WIRE NETTING – TO BS443			
SIZE	10 MTR ROLL	25 MTR ROLL	50 MTR ROLL
600mm x 13mm x 22G	•	•	•
600mm x 25mm x 20G	•	•	•
600mm x 50mm x 19G	•	•	•
900mm x 13mm x 22G	•	•	•
900mm x 19mm x 20G	•	•	•
900mm x 19mm x 22G	•	•	•
900mm x 25mm x 20G	•	•	•
900mm x 25mm x 22G	•	•	•
900mm x 50mm x 19G	•	•	•
1200mm x 19mm x 22G	•	•	•
1200mm x 19mm x 20G	•	•	•
1200mm x 25mm x 20G	•	•	•
1200mm x 50mm x 19G	•	•	•
1800mm x 25mm x 20G	•	•	•
1800mm x 50mm x 19G	•	•	•
STAINLESS STEEL WIRE NETTING			
900mm x 25mm x 20G			•
900mm x 25mm x 22G			•

Sealumet (Australia) Pty Limited

Mailing Address : PO Box 2218, Warwick, Perth, WA, 6024

Warehouse : Unit 2, 6 Langar Way, Landsdale, Perth, WA - 6065

Telephone : +618 6201 6153, Fax : +618 9303 4560

E-mail: enquiries@sealumet.com Website: www.sealumet.com

DISCLAIMER

These data sheets are based on specifications, data and test results at time of publication. No guarantee as to completeness, accuracy or results is either expressed or implied. The suitability for an intended use is the responsibility of the user. As choice of material, method of application and site conditions are beyond our control we accept no liability for direct or consequential damages. Any material proved to be defective within the published shelf life* will be replaced. *From date of supply.